



2019 Tandem Tech INSPECTOR'S FORM

THIS FORM IS TO BE COMPLETED ONLY BY AN AUTHORIZED SONOMA DRIFT TECH CENTER OR
AUTHORIZED SONOMA DRIFT TECH PERSONNEL DURING ANNUAL INSPECTION.

Note: Not all items applicable to all classes of vehicles. A number of items are not required

RULE BOOK / TECH DISCLAIMER - The rules and/or tech regulations set forth herein are designed to provide for the orderly conduct of racing events and to establish minimum acceptable requirements for such events. These rules shall govern the condition of all events, and by participating in these events, all participants are deemed to have complied with these rules. **NO EXPRESSED OR IMPLIED WARRANTY OF SAFETY SHALL RESULT FROM . PUBLICATIONS OF OR COMPLIANCE WITH THESE RULES ANDIOR REGULATIONS.** They are intended as a guide for the conduct of the sport and are in no way a guarantee against injury or death to a participant, spectator, tech official or official. The race director shall be empowered to permit reasonable and appropriate deviation from any of the specifications herein or impose any further restrictions that in his opinion do not alter the minimum acceptable requirements. **NO EXPRESSED OR IMPLIED WARRANTY OF SAFETY SHALL RESULT FROM SUCH ALTERATION OF SPECIFICATIONS.** Any interpretation or deviation of these rules is left to the discretion of the officials. Their decision is final.

VEHICLE EXTERIOR

- Crash bar or factory bumper required on front end
- Tow hooks, front and rear
- No sharp edges

ENGINE COMPARTMENT

- Clean
- Coolant overflow
- Oil overflow
- No fluid leaks
- Battery secured
- Battery positive terminal covered
- Batteries in driver's compartment needs to be in a sealed box (unless the battery is dry cell type)
- Starter positive terminal covered
- No loose wires
- Condition of hoses
- No firewall holes
- Brake fluid level/condition
- Engine mounts
- Operation of hood release/pins

ROLL CAGE

- Cage number stamped _____
- Main hoop 1 piece, 4 bends max
- Rear down tubes not bent
- Door bars
- Diagonal bar
- All mandrel bends
- Mounting plates
- 360 welds on required bars
- General condition
- Padding on contact areas
- Broomstick test – open cars

HAND EXTINGUISHER

- Within driver's reach
- 2lb minimum ABC, full
- Metal mounting plate/bracket
- Mounting bracket bolted in

DRIVER COMPARTMENT

- If fuel cell is located in driver compartment, a fire wall is required
- Electrical cutoff switch function
- Cutoff switch terminals covered
- No sharp edges

DRIVER SEAT

- Factory seat or better
- Mounted securely

HARNES

- Mounting points
- Condition of webbing
- Shoulder belt mounting no more than 20 degrees from horizontal
- Lap belt mounting

DRIVER EMERGENCY EXIT TIME

- Exit within 10 seconds starting in as-raced condition through door

STEERING AND SUSPENSION

- No significant play in steering, bearings or suspension
- If keyless start column lock is removed

Valid for 2 years from inspection date

Inspector Name and Number

Vehicle Log Book Number

Signature or Shop Stamp:

Date: